



ZL75H WHEEL LOADER SPECIFICATIONS

- Equipped with reliable original Cummins engine
- KD switch allows better efficiency & easy operation
- Reliable ZF transmission case and Torque Converter
- Famous original ZF wet-type axles with multi-disc limited-slip differentials deliver maximum traction in changing traction conditions
- Bucket automatic leveling ability
- Combined seal cylinder obtains high seal performance and more reliability
- Dual brake valve & dual pipe full hydraulic brake and central lubrication

| Overall Dimension | | |
|-------------------|-------------------------------|----------|
| 1 | Length(with bucket on ground) | 8696(mm) |
| 2 | Width(to outside of wheels) | 3099(mm) |
| 3 | Bucket width | 3266(mm) |
| 4 | Height(To the top of the cab) | 3730(mm) |
| 5 | Wheel base | 3400(mm) |
| 6 | Tread | 2350(mm) |

Address: No. 10 Changlin Road, Changzhou, Jiangsu, China 213002
 Tel: +86-519-86781288 86752400 86781018
 Website: www.changlin.com.cn; www.cn-changlin.com

中国，江苏，常州，常林路 10 号
 Fax: +86-519-86781387
 Email: changlinexport@yahoo.com
 sales@changlin.com.cn

| | | |
|--|---------------------------------------|--|
| 1 | Model | ZF4WG308 |
| 2 | Type | Power shift, spur gear constant-mesh |
| 3 | Gear shift position | 4 Forward and 3 reverse gears |
| 3. Axle and Tire | | |
| 1 | Type of main reducer | single stage |
| 2 | Gear ratio of main reducer | 4.777 |
| 3 | Type of final reducer | single stage planetary |
| 4 | Gear of ratio of final reducer | 5.167 |
| 5 | Total ratios | 24.685 |
| 6 | Size of tyre | 26.5-25 -20PR (L-3) |
| Working Device Hydraulic System | | |
| 1 | Model of oil pump(include brake pump) | 322-9529-157 |
| 2 | System pressure | 21(MPa) |
| 3 | Model of Muti-way directional valve | 7130-B97(HUSCO) |
| 4 | Model of pilot valve | 406-1044-1145(HUSCO) |
| 5 | (d*I)Dimension of lifting cylinder | Φ180*100*767(mm) |
| 6 | (D*I)Dimension of tilting cylinder | Φ210*110*555(mm) |
| Steering System | | |
| 1 | Type | Middle articulated frame. full hydraulic power |
| 2 | Model of steering pump | 322-9114-008 |
| 3 | Model of redirector | 150-1084 |
| 5 | System pressure | 17.5MPa |
| 6 | Dimension of steering cylinder | Φ100*50*441(mm) |

Address: No. 10 Changlin Road, Changzhou, Jiangsu, China 213002
 Tel: +86-519-86781288 86752400 86781018
 Website: www.changlin.com.cn; www.cn-changlin.com

中国, 江苏, 常州, 常林路 10 号
 Fax: +86-519-86781387
 Email: changlinexport@yahoo.com
 sales@changlin.com.cn

